STONEX

X200GO Laser Scanner

3D Handheld Laser Scanner



STONEX SLAM

X200GO TECHNICAL FEATURES

The X200GO is the latest generation system based on the SLAM technology, capable of covering any customer need. The range of up to 300 metres and a rotating head that maximises the coverage of the laser beam make it versatile for any environment. Equipped with 2 cameras and RTK receiver for real-time point cloud colouring and orientation. The two cameras provide navigable and measurable panoramic cameras superimposed on the 3D model. The system allows for the survey of static scans in X-Whizz mode, automatically aligned to the SLAM survey.
Backpack, shoulders hook, car mount and holder for DJI M350 can complete the system.

LIDAR	
Sensor Model	Hesai XT32M2X
Max Range	300 m
Min Range	0.5 m
Return number	3
Scanning Point Frequency	640.000 pts/s (single return) 1.280.000 pts/s (dual return) 1.920.000 pts/s (triple return)
Field of view	360° x 290°
Laser Class	Class 1 eye-safe per IEC/EN 60825-1:2014
Channels	32
Wavelength	905nm

COLOR CAMERA	
N° of pixels	24 Mpx (2 cameras, 12 Mpx each)
Diagonal FOV	210°
Focal length	1.26 mm
Resolution	8000x3000 px
Sensor size	1/2.3 inch
Pixel size	1.55 μm

GNSS RECEIVER	
Satellites Signal	GPS L1 C/A/L2P(Y)/L2C/L5 GLONASS G1/G2 Galileo E1/E5A/E5B BDS B1I/B2I/B3I QZSS L1/L2/L5
DGPS (RMS)	Horizon 0.4 m+1 ppm Vertical 0.8 m+1 ppm
RTK (RMS)	Horizon 0.8cm+1ppm Vertical 1.5cm+1ppm
Speed accuracy (RMS)	0.03m/s

SYSTEM	
Relative accuracy	Up to 6mm[1]
Global accuracy	Up to 2cm[1] 5cm on UAV platform[1]
Control point support	Ground & wall
Data storage	512GB SSD
Communication	Wi-fi, Bluetooth, USB type-c, Lemo connector
Operating mode	SLAM & X-Whizz modes, Real-time visualisation, colouring and orientation
Processing mode	Real-time processing Post-processing with GO*post*

ELECTRICAL SPECIFICATION	
Power consumption	26W
System supply voltage	20V
Operating time	1.2 h (single battery)[2]
Battery weight	400 g
External power	USB type-c
Battery input voltage	5-20V
Battery output voltage	10.8V
Battery capacity	3000mAh

PHYSICAL SPECIFICATION	
Weight	1.4 kg (without battery)
Size (with handle)	403.6 mm x 173.8mm x 170mm
Operating temperature	-20°C to +50°C (-4°F to 122°F)
Operating humidity	<95%
Waterproof/Dustproof	IP54

PLATFORM/EXTENSION	
Backpack	✓
GNSS module	Integrated
360° camera	Integrated Insta X360 X4/X4air/X5; DJI Osmo360
Vehicle mount	✓
UAV	DJI M300/350 (RTK) DJI M400 (PPK)
Radio Modem	Stonex SR02


1. Environment dependent
2. SLAM only, no external platforms

BUNDLED SOFTWARE

GOapp

GOapp is dedicate mobile application for Stonex SLAM scanners, to manage projects, real time point cloud display, image preview, firmware upgrade and other operations. The APP runs on Android and iOS operating system.

Min requirements: Android 10 | iOS 12



GOpost

Windows post processing software which performs optimization processing, colouring of point clouds and creation of panoramic images. You can also import control points to georeference the point cloud.

Minimum requirements: Windows 10-11; 64bit; Intel processor i7; 16GB RAM; NVIDIA RTX2060
Recommended requirements: Windows 10-11; 64bit; Intel processor i7; 32GB RAM; NVIDIA RTX4060

STONEX AUTHORIZED DEALER

Illustrations, descriptions and technical specifications are not binding and may change

STONEX®
Viale dell'Industria 53 - 20037 Paderno Dugnano (MI) - Italy
Phone +39 02 78619201
www.stonex.it | info@stonex.it

MK.1.1 - REV.02 - X200GO - FEBRUARY 2026 - VER.03